

General characteristics

| | |
|-------------------|--|
| Switching diagram | 25 - 1-phase motor reversing switch with spring return |
| N° of elements | 2 |
| Mounting form | U47 - Snap on front mounting with black handle for hole diam. 22mm finxing |

Contact characteristics

| | | | |
|---|--------------------|----|-----------|
| Rated insulation voltage U_i | IEC/EN | V | 690 |
| | UL/CSA | V | 600 |
| Rated impulse withstand voltage U_{imp} | | kV | 6 |
| Conventional free air thermal current I_{th} | IEC/EN | A | 16 |
| | UL/CSA | A | 12 |
| Rated operational voltage | | V | 440 |
| Rated operational impulse voltage | | kV | 4 |
| Maximum fuse size for short-circuit protection I_n (gG) | 10kA | A | 16 |
| | 15kA | A | 16 |
| | 25kA | A | 16 |
| Rated short time current I_{cw} | 1s | kA | 250 |
| | | | 10/5 mA/V |
| Conductivity | | | 10/5 mA/V |
| Operational current I_e IEC/EN | AC1/AC21A | A | 16 |
| | AC15 | | |
| | 110V | A | 10 |
| | 220/230V | A | 8 |
| | 380/400V | A | 4 |
| | 660/690V | A | 1.5 |
| Rated operational power in AC | Three-phase AC-3 | | |
| | | | |
| | 220/230V | kW | 3.5 |
| | 380/440V | kW | 4.5 |
| | 500/690V | kW | 5.5 |
| | Single-phase AC-3 | | |
| | 110V | kW | 0.55 |
| | 220/230V | kW | 1.5 |
| | 380/440V | kW | 2.2 |
| | Three-phase AC23A | | |
| | 220/230V | kW | 3.7 |
| | 380/440V | kW | 6.5 |
| | 500/690V | kW | 7.5 |
| | Single-phase AC23A | | |
| | 110V | kW | 0.75 |
| | 220/230V | kW | 1.8 |
| | 380/440V | kW | 3 |

Rated operational current in DC

| | | | | |
|--|------|-----------------|-------------------|----|
| DC21A | | | | |
| | 48V | A | 16 | |
| | 60V | A | 16 | |
| | 110V | A | 4 | |
| | 220V | A | 0.6 | |
| | 440V | A | 0.25 | |
| DC23A (poles in series) | | | | |
| | 24V | A | 16 (1) | |
| | 48V | A | 16 (2) | |
| | 60V | A | 16 (3) | |
| | 110V | A | 10 (3) | |
| | 220V | A | 7 (4) | |
| DC13 | | | | |
| | 24V | A | 16 | |
| | 48V | A | 14 | |
| | 60V | A | 10 | |
| | 110V | A | 1 | |
| | 220V | A | 0.4 | |
| | 440V | A | 0.15 | |
| Power dissipation | | W | 0.6 | |
| Mechanical features | | | | |
| Terminals screw | | | | 3M |
| Tightening torque for terminals max | | Nm | 0.5 | |
| Conductor size | | | | |
| AWG - Rigid cable | | | | |
| | min | AWG | 20 | |
| | Max | AWG | 12 | |
| AWG - Flexible cable | | | | |
| | min | AWG | 20 | |
| | Max | AWG | 12 | |
| Conductor size (IEC) - Flexible cable | | | | |
| | min | mm ² | 0.5 | |
| | Max | mm ² | 2.5 | |
| Conductor size (IEC) - Rigid cable | | | | |
| | min | mm ² | 0.5 | |
| | Max | mm ² | 2.5 | |
| Mechanical life | | cycles | 1X10 ⁶ | |
| UL technical data | | | | |
| Motor power for direct-on-line control | | | | |
| for three-phase motor | | | | |
| | 120V | HP | 1.5 | |
| | 240V | HP | 3 | |
| | 480V | HP | 5 | |
| | 600V | HP | 5 | |
| for single-phase motor | | | | |
| | 120V | HP | 0.75 | |
| | 240V | HP | 1 | |
| Ambient conditions | | | | |
| Temperature | | | | |
| Operating temperature | | | | |
| | min | °C | -25 | |
| | max | °C | +55 | |
| Storage temperature | | | | |
| | min | °C | -40 | |

max °C +70

| Resistance & Protection | |
|-------------------------|--------------------------------------|
| Frontal IP degree | IP65 |
| Terminals IP degree | IP20 |
| ETIM classification | |
| ETIM 8.0 | EC001029 - Selector switch, complete |