# GX1691O48

ROTARY CAM SWITCH GX SERIES, ON-OFF SWITCH 2 POLES 16A, MODULAR SERVICE COVER FOR 35MM DIN REAIL MOUNTING WITH BLACK HANDLE, FRONT PLATE 45X54MM

## General characteristics

| | |
|---|---|
| Switching diagram | 91 - ON/OFF switch 2 poles |
| N° of elements | 1 |
| Mounting form | O48 - Modular service cover for 35mm din rail mounting with black handle |

## Contact characteristics

| | | | |
|---|---|---|---|
| Rated insulation voltage Ui | | | |
| | IEC/EN | V | 690 |
| | UL/CSA | V | 600 |
| Rated impulse withstand voltage Uimp | | kV | 6 |
| Conventional free air thermal current Ith | | | |
| | IEC/EN | A | 16 |
| | UL/CSA | A | 12 |
| Rated operational voltage | | V | 440 |
| Rated operational impulse voltage | | kV | 4 |
| Maximum fuse size for short-circuit protection In (gG) | | | |
| | 10kA | A | 16 |
| | 15kA | A | 16 |
| | 25kA | A | 16 |
| Rated short time current Icw | | | |
| | 1s | kA | 250 |
| Conductivity | | | 10/5 mA/V |
| Operational current Ie IEC/EN | | | |
| AC1/AC21A | | | |
| | | A | 16 |
| AC15 | | | |
| | 110V | A | 10 |
| | 220/230V | A | 8 |
| | 380/400V | A | 4 |
| | 660/690V | A | 1.5 |
| Rated operational power in AC | | | |
| Three-phase AC-3 | | | |
| | 220/230V | kW | 3.5 |
| | 380/440V | kW | 4.5 |
| | 500/690V | kW | 5.5 |
| Single-phase AC-3 | | | |
| | 110V | kW | 0.55 |
| | 220/230V | kW | 1.5 |
| | 380/440V | kW | 2.2 |
| Three-phase AC23A | | | |
| | 220/230V | kW | 3.7 |
| | 380/440V | kW | 6.5 |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

| | | | | |
|---|---|---|---|---|
| | | 500/690V | kW | 7.5 |
| | Single-phase AC23A | | | |
| | | 110V | kW | 0.75 |
| | | 220/230V | kW | 1.8 |
| | | 380/440V | kW | 3 |
| Rated operational current in DC | | | | |
| | DC21A | | | |
| | | 48V | A | 16 |
| | | 60V | A | 16 |
| | | 110V | A | 4 |
| | | 220V | A | 0.6 |
| | | 440V | A | 0.25 |
| | DC23A (poles in series) | | | |
| | | 24V | A | 16 (1) |
| | | 48V | A | 16 (2) |
| | | 60V | A | 16 (3) |
| | | 110V | A | 10 (3) |
| | | 220V | A | 7 (4) |
| | DC13 | | | |
| | | 24V | A | 16 |
| | | 48V | A | 14 |
| | | 60V | A | 10 |
| | | 110V | A | 1 |
| | | 220V | A | 0.4 |
| | | 440V | A | 0.15 |
| Power dissipation | | | W | 0.6 |
| **Mechanical features** | | | | |
| Terminals screw | | | | 3M |
| Tightening torque for terminals max | | | Nm | 0.5 |
| Conductor size | | | | |
| | AWG - Rigid cable | | | |
| | | min | AWG | 20 |
| | | Max | AWG | 12 |
| | AWG - Flexible cable | | | |
| | | min | AWG | 20 |
| | | Max | AWG | 12 |
| | Conductor size (IEC) - Flexible cable | | | |
| | | min | mm² | 0.5 |
| | | Max | mm² | 2.5 |
| | Conductor size (IEC) - Rigid cable | | | |
| | | min | mm² | 0.5 |
| | | Max | mm² | 2.5 |
| Mechanical life | | | cycles | 1X10⁶ |
| **UL technical data** | | | | |
| Motor power for direct-on-line control | | | | |
| | for three-phase motor | | | |
| | | 120V | HP | 1.5 |
| | | 240V | HP | 3 |
| | | 480V | HP | 5 |
| | | 600V | HP | 5 |
| | for single-phase motor | | | |
| | | 120V | HP | 0.75 |
| | | 240V | HP | 1 |
| **Ambient conditions** | | | | |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

# GX1691O48

ROTARY CAM SWITCH GX SERIES, ON-OFF SWITCH 2 POLES 16A, MODULAR SERVICE COVER FOR 35MM DIN REAIL MOUNTING WITH BLACK HANDLE, FRONT PLATE 45X54MM

Temperature

| | | | |
|---|---|---|---|
| Operating temperature | | | |
| | min | °C | -25 |
| | max | °C | +55 |
| Storage temperature | | | |
| | min | °C | -40 |
| | max | °C | +70 |

## Resistance & Protection

| | |
|---|---|
| Frontal IP degree | IP65 |
| Terminals IP degree | IP20 |

## Dimensions




| Series | L1 | | |
|---|---|---|---|
| | 1 | 2 | 3 |
| GX16 | 33 | 41.5 | 50 |
| GX20 | 33 | 41.5 | 50 |

## Wiring diagrams




## Certifications and compliance

Compliance

| |
|---|
| CSA C22.2 n° 14 |
| IEC/EN/BS 60947-1 |
| IEC/EN/BS 60947-3 |
| IEC/EN/BS 60947-5-1 |
| IEC/EN/BS 61058-1 |
| UL60947-4-1 |

Certificates

| |
|---|
| cULus |
| EAC |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding

## ETIM classification

| | |
|---|---|
| ETIM 8.0 | EC001105 - Off-load switch |


The characteristics described in this document are subject to updates or modifications at any time. The descriptions, technical and functional information, illustrations and instructions in this brochure are purely illustrative, and are consequently not contractually binding