



General characteristics

General characteristics

Housing Material	Polymer thermoplastic
Key shape	Angled "T"

Contact characteristics

Type of contact	2NO+1NC Slow action
Thermal current I _{th}	A 10
IEC/EN 60947-5-1 designation	A600 Q600
Rated insulation voltage U _i	V 690
Rated impulse withstand voltage U _{imp}	kV 6
Insulation class	II
Short-circuit protection with fuse	Class/A 10 gG/SC QUICK FUSE
Switching speed	

min	m/s	0.5
max	m/s	1.5

IEC Conventional free air thermal current I _{th} ≤ 40°C	A 10
Resistance per pole (average value)	mΩ <10

Operations

Mechanical life	cycles	100000
B10d	cycles	100000
Mechanical operation	cycles/h	3600

Output characteristics

Mechanical life	cycles	100000
-----------------	--------	--------

Mechanical features

Operating head fixing	Locking bayonet insert
-----------------------	------------------------

Operating torque	N 8
	lb 1.8


Tightening torque (Max)			
Switch fixing		Nm	2.5
		lbin	22.1
Contact terminals		Nm	0.8
		lbin	7
Body lid screw fixing		Nm	0.8
		lbin	7

Conductor section		
AWG/Kcmil	min	16

LIMIT SWITCH, K SERIES, KEY OPERATED, 1 BOTTOM CABLE ENTRY. DIMENSIONS TO EN 50047, PLASTIC BODY, CONTACTS 2NO+1NC SLOW ACTION. ANGLED "T" KEY


IEC	max		14
	min	mm ²	1.5
	max	mm ²	2.5
Cable connection			Self-releasing screw terminal
Cable entry			M20 on the bottom
Weight			g 96
Ambient conditions			
Pollution degree			3
Temperature			
Operating temperature			
		min °C	-25
		max °C	+70
Storage temperature			
		min °C	-40
		max °C	+70

Dimensions



Wiring diagrams

Slow action



2NO + 1NC

Certifications and compliance

Compliance

CSA C22.2 n° 14

EN 50047

IEC/EN 60204-1

IEC/EN 60947-1

IEC/EN 60947-5-1

UL508

Certificates

CCC

cULus

EAC

ETIM classification

ETIM 8.0

EC000030 - End switch