



General characteristics

Colour	Grey/Yellow with red mushroom	
Type of positions	Pull to release	
Resistance value	KΩ	≤0.025
Material	PC-ABS for button and control station. Chrome-plasted zamak for metal operator frame	
IEC degree of protection	IP65	

Electrical characteristics



Rated insulation voltage Ui IEC/EN	V	690
IEC Conventional free air thermal current Ith ≤ 40°C	A	10
Rated frequency	Hz	50
Conductivity	5V 10mA	
UL/CSA and IEC/EN 60947-5-1 designation	A600 Q300	
Operating current AC15		
	12V	A 6
	24V	A 6
	48V	A 6
	120V	A 6
	240V	A 3
	400V	A 1.9
	480V	A 1.5
	500V	A 1.4
	600V	A 1.2
Operating current DC13		
	12V	A 3
	24V	A 3
	48V	A 1.5
	125V	A 0.55
	250V	A 0.27
	440V	A 0.15
	500V	A 0.13
	600V	A 0.1

Mechanical features


Operating force	kg-lb	≤2.6Nm	
Mechanical life	cycles	1000000	
Tightening torque for terminals max	Nm	0.5 ... 0.8 Nm	
Conductor section	IEC		
	min	mm²	0.5
	max	mm²	2.5
Operating position			

		allowable	Any
Ambient conditions			
Temperature			
Operating temperature		min	°C -25
		max	°C +75
Storage temperature			
		min	°C -40
		max	°C +85

Dimensions



Wiring diagrams



Certifications and compliance

Compliance		IEC60947-5-1
Certificates		/

ETIM classification

ETIM 8.0	EC002034 - Emergency stop complete
----------	--