



General characteristics

Colour	Grey with black mushroom		
Type of positions	Momentary		
Resistance value	KΩ	≤0.025	
Material	PC-ABS for button and control station. PA66 for plastic operator frame		
IEC degree of protection	IP65		

Electrical characteristics

Rated insulation voltage U_i IEC/EN	V	690	
IEC Conventional free air thermal current $I_{th} \leq 40^\circ\text{C}$	A	10	
Rated frequency	Hz	50	
Conductivity	5V 10mA		
UL/CSA and IEC/EN 60947-5-1 designation	A600 Q300		
Operating current AC15	12V	A	6
	24V	A	6
	48V	A	6
	120V	A	6
	240V	A	3
	400V	A	1.9
	480V	A	1.5
	500V	A	1.4
Operating current DC13	600V	A	1.2
	12V	A	3
	24V	A	3
	48V	A	1.5
	125V	A	0.55
	250V	A	0.27
	440V	A	0.15
	500V	A	0.13
600V	A	0.1	

Mechanical features

Operating force	kg-lb	≤2.6Nm	
Mechanical life	cycles	1000000	
Tightening torque for terminals max	Nm	0.5 ... 0.8 Nm	
Conductor section	IEC	min	mm ² 0.5
		max	mm ² 2.5
		Operating position	allowable

Ambient conditions

Temperature



Operating temperature

min	°C	-25
max	°C	+75

Storage temperature

min	°C	-40
max	°C	+85

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

IEC60947-5-1

Certificates

/

ETIM classification

ETIM 8.0

EC002034 -
Emergency stop
complete