



#### General characteristics

|                          |                      |
|--------------------------|----------------------|
| Colour                   | Blue                 |
| Type of positions        | Flush pushbutton     |
| Material                 | Polyamide            |
| IEC degree of protection | IP66, IP67 and IP69K |

#### Mechanical features

|                                           |        |                          |
|-------------------------------------------|--------|--------------------------|
| Operating force                           | kg-lb  | <0.5Kg / 1.1lb           |
| Mechanical life - spring return actuators | cycles | 5000000                  |
| Fixing                                    |        | Without mounting adapter |
| Mounting adapter                          |        | LPXAU120                 |
| Weight                                    | g      | 25                       |


#### UL technical data

|                         |                              |
|-------------------------|------------------------------|
| UL degree of protection | Type1, 2, 3R, 4, 4X, 12, 12K |
|-------------------------|------------------------------|

#### Ambient conditions

|                       |     |    |     |
|-----------------------|-----|----|-----|
| Temperature           |     |    |     |
| Operating temperature |     |    |     |
|                       | min | °C | -25 |
|                       | max | °C | +70 |
| Storage temperature   |     |    |     |
|                       | min | °C | -40 |
|                       | max | °C | +85 |

#### Dimensions



#### Certifications and compliance

|              |                     |
|--------------|---------------------|
| Compliance   |                     |
|              | CSA C22.2 n° 14     |
|              | IEC/EN/BS 60947-1   |
|              | IEC/EN/BS 60947-5-1 |
|              | UL508               |
| Certificates |                     |
|              | CCC                 |
|              | cULus               |
|              | EAC                 |

---

RINA

ETIM classification

ETIM 8.0

EC000221 -  
Front element for  
push button