



#### General characteristics

|                          |                                       |
|--------------------------|---------------------------------------|
| Colour                   | Yellow                                |
| Type of positions        | Flush pushbutton.<br>Push on-push off |
| Material                 | Aluminium and<br>zinc alloy           |
| IEC degree of protection | IP66, IP67 and<br>IP69K               |

#### Mechanical features

|                                       |        |                             |
|---------------------------------------|--------|-----------------------------|
| Operating force                       | kg-lb  | <0.5Kg / 1.1lb              |
| Mechanical life - Push-Push actuators | cycles | 500000                      |
| Fixing                                |        | Without mounting<br>adapter |
| Mounting adapter                      |        | LPXAU120M                   |


#### UL technical data

|                         |                                 |
|-------------------------|---------------------------------|
| UL degree of protection | Type1, 2, 3R, 4,<br>4X, 12, 12K |
|-------------------------|---------------------------------|

#### Ambient conditions

|                       |     |    |     |
|-----------------------|-----|----|-----|
| Temperature           |     |    |     |
| Operating temperature |     |    |     |
|                       | min | °C | -25 |
|                       | max | °C | +70 |
| Storage temperature   |     |    |     |
|                       | min | °C | -40 |
|                       | max | °C | +85 |

#### Dimensions



#### Certifications and compliance

|              |                     |
|--------------|---------------------|
| Compliance   |                     |
|              | CSA C22.2 n° 14     |
|              | IEC/EN/BS 60947-1   |
|              | IEC/EN/BS 60947-5-1 |
|              | UL508               |
| Certificates |                     |
|              | cULus               |

#### ETIM classification

|          |                                                |
|----------|------------------------------------------------|
| ETIM 8.0 | EC000221 -<br>Front element for<br>push button |
|----------|------------------------------------------------|