



#### General characteristics

|                          |                                |
|--------------------------|--------------------------------|
| Colour                   | Black                          |
| Type of positions        | 1 > 0 - 2, key extraction in 0 |
| Material                 | Aluminium and zinc alloy       |
| IEC degree of protection | IP66, IP67 and IP69K           |

#### Mechanical features

|                  |                          |         |
|------------------|--------------------------|---------|
| Mechanical life  | cycles                   | 1000000 |
| Fixing           | Without mounting adapter |         |
| Mounting adapter | LPXAU120M                |         |


#### UL technical data

|                         |                              |
|-------------------------|------------------------------|
| UL degree of protection | Type1, 2, 3R, 4, 4X, 12, 12K |
|-------------------------|------------------------------|

#### Ambient conditions

|                       |     |    |     |
|-----------------------|-----|----|-----|
| Temperature           |     |    |     |
| Operating temperature |     |    |     |
|                       | min | °C | -25 |
|                       | max | °C | +70 |
| Storage temperature   |     |    |     |
|                       | min | °C | -40 |
|                       | max | °C | +85 |

#### Dimensions



#### Certifications and compliance

|              |  |                     |
|--------------|--|---------------------|
| Compliance   |  | CSA C22.2 n° 14     |
|              |  | IEC/EN/BS 60947-1   |
|              |  | IEC/EN/BS 60947-5-1 |
|              |  | UL508               |
| Certificates |  | cULus               |

#### ETIM classification

|          |                           |
|----------|---------------------------|
| ETIM 8.0 | EC002611 - Control switch |
|----------|---------------------------|