



Electrical features

| | | |
|---|----|----------|
| Relay adj range | A | 6.3-10 |
| IEC technical characteristics ($\leq 440V$) | | |
| | le | A 10 |
| | kW | kW 3...4 |

Components

| | |
|-------------------------------------|----------|
| Starter enclosure standard supplied | M1RA |
| Contactor standard supplied | BF0910A |
| Thermal relay standard supplied | RF381000 |

UL technical data

| | |
|-------------------------|--------------------|
| UL degree of protection | Type 1, 12K, 4, 4X |
|-------------------------|--------------------|

Mechanical features

| | | |
|--------|---|-----|
| Weight | g | 995 |
|--------|---|-----|


Ambient conditions

| | | | |
|-----------------------|-----|----|-----|
| Operating temperature | | | |
| | min | °C | -25 |
| | max | °C | +60 |
| Storage temperature | | | |
| | min | °C | -40 |
| | max | °C | +70 |


Resistance & Protection

| | |
|--------------------------|------|
| IEC degree of protection | IP65 |
|--------------------------|------|

Dimensions



Wiring diagrams



R = Reset; I = Start; O = Stop

Certifications and compliance

Compliance

IEC/EN 60947-1
IEC/EN 60947-4-1
UL508 CSA C22.2 n° 14

Certificates

CSAus
cULus
EAC

ETIM classification

ETIM 8.0

EC001037 -
Motor
starter/Motor
starter
combination