



General characteristics

Number of poles	Nr.	3
Overvoltage category		III
Pollution degree		3
Frontal IP degree		IP20
Type of release		Thermal
Protection fuse		
	gG (IEC)	A 80
	aM (IEC)	A 50
	K5 (UL)	A 150
Phase failure detection		no
Reset mode		Manual

Power circuit characteristics

Rated insulation voltage U_i IEC/EN	V	690
Rated impulse withstand voltage U_{imp}	kV	8
Rated operational voltage	V	690
Operational frequency		
	min	Hz 0
	max	Hz 400

Operational current I_e		
	Operational current min	A 28
	Operational current max	A 42

Tripping class		10A
Test Button		Yes
Trip indicator		yes

Terminals		
	type	Yoke clamp
	screw	M5
	width	mm 9
	tool	Phillips 2


Tightening torque for terminals		
	min	Nm 3.9
	max	Nm 3.9
	min	Ibin 2.88
	max	Ibin 2.88

Conductor section		
	AWG/kcmil max	2


Auxiliary circuit characteristics

Auxiliary contacts		
	NO	Nr. 1
	NC	Nr. 1
Auxiliary Rated insulation voltage U_i IEC/EN	V	690
Auxiliary Rated impulse withstand voltage U_{imp}	kV	6
Auxiliary Rated operational voltage	V	690
Operating current AC15		

	24V	A	3
	120V	A	3
	240V	A	1.5
	380V	A	0.95
	480V	A	0.75
	500V	A	0.72
	600V	A	0.6
<hr/>			
Operating current DC13			
	125V	A	0.11
	600V	A	0.22
<hr/>			
IEC Conventional free air thermal current I _{th} ≤ 40°C		A	10
<hr/>			
Terminals			
	Auxiliary circuit type		screw and washer
	Auxiliary circuit screw		M3,5
	Auxiliary circuit width	mm	8
	Auxiliary circuit tool		Phillips 1
<hr/>			
Conductor section			
	Auxiliary circuit Flexible w/o lug max	mm ²	2.5
	Auxiliary circuit Flexible c/w lug max	mm ²	2.5
<hr/>			
Tightening torque for terminals			
	Auxiliary circuit min	Nm	1
	Auxiliary circuit max	Nm	1
	Auxiliary circuit min	Ibin	0.74
	Auxiliary circuit max	Ibin	0.74
<hr/>			
UL/CSA and IEC/EN 60947-5-1 designation			B600-P600
<hr/>			
Ambient conditions			
Operating temperature			
	min	°C	-20
	max	°C	55
<hr/>			
Storage temperature			
	min	°C	-55
	max	°C	80
<hr/>			
Compensation temperature			
	min	°C	-15
	max	°C	55
<hr/>			
Max altitude		m	3000
<hr/>			
Mechanical features			
Operating position			
	normal allowable		Vertical plan ±30°
<hr/>			
Fixing			Direct mounting on BF40... BF94...
<hr/>			
Weight		g	365
<hr/>			
UL technical data			
Full-load current (FLA) for three-phase AC motor			
	at 480V	A	42
	at 600V	A	42
<hr/>			
Dimensions			



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 14

IEC/EN 60947-1

IEC/EN 60947-4-1

UL508

Certifications

cULus

ETIM classification

ETIM 8.0

EC000106 -
Thermal overload
relay