





Electrical features			
Number of poles	Nr.		3
Magnetic protection			yes
Thermal protection			yes
Phase failure detection			yes
Rated insulation voltage $U_i$ IEC/EN	V		690
Rated impulse withstand voltage $U_{imp}$	kV		6
Rated frequency	Hz		50/60
Thermal trip adjustment range			17...23
Rated current ( $I_n$ )	A		23
Magnetic tripping			13 x $I_n$
Power dissipation per pole	min	W	1.86
	max	W	3.41
Operational short-circuit current breaking capacity ( $I_{cs}$ ) at AC	230V	kA	100
	400V	kA	25
	440V	kA	5
	500V	kA	5
	690V	kA	2
Maximum short-circuit current breaking capacity ( $I_{cu}$ ) at AC	230V	kA	100
	400V	kA	50
	440V	kA	10
	500V	kA	10
	690V	kA	4
Tripping class			10A
IEC Utilization category			A
Operations			
Mechanical life		cycles	100000
Electrical life		cycles	100000
Mechanical features			
Tightening torque for terminals	min	Nm	2.5
	max	Nm	3
	min	lbin	22
	max	lbin	26.5
Max number of wires simultaneously connectable	Nr.		2
Conductor section	AWG/Kcmil	min	16
		max	8
Flexible w/o lug conductor section	min	mm <sup>2</sup>	1
	max	mm <sup>2</sup>	10

Flexible c/w lug conductor section			
	min	mm <sup>2</sup>	1
	max	mm <sup>2</sup>	10
Flexible with insulated spade lug conductor section			
	min	mm <sup>2</sup>	1
	max	mm <sup>2</sup>	10
Screwdriver			PH2
Power terminal protection according to IEC/EN 60529			IP20 on front
Cable stripping length			
	main circuit	mm	10
<b>Ambient conditions</b>			
Temperature			
Operating temperature			
	min	°C	-20
	max	°C	+60
Storage temperature			
	min	°C	-50
	max	°C	+80
Compensation temperature			
	min	°C	-20
	max	°C	+50
Max altitude			m 3000
Operating position			normal allowable Vertical plan Any
Fixing			Screw / DIN rail 35mm
Weight			g 390
<b>UL technical data</b>			
Motor Disconnect			
	at 240V	kA	30
	at 480V	kA	30
	at 600V	kA	30
	protection		200A class J
Group Motor Installation			
	at 480V	kA	30
	at 600V	kA	30
	protection		200A class J
Maximum UL/CSA horsepower ratings single-phase			
	110V-120V	HP	1.5
	220V-240V	HP	3
Maximum UL/CSA horsepower ratings three-phase, 3-pole			
	200V-208V	HP	5
	220V-240V	HP	7.5
	440V-480V	HP	15
	550V-600V	HP	20

**Dimensions**



**Wiring diagrams**



**Certifications and compliance**

Certifications

CSA C22.2 n° 14

IEC/EN 60947-1

IEC/EN 60947-2

IEC/EN 60947-4-1

UL508

Compliance

cULus

EAC

ETIM classification

ETIM 8.0

EC000074 -  
Motor protection  
circuit-breaker