



Code produit	MAA1016A10	Connectable conductor cross section fine-strand without cable end sleeve	1.5 - 10 mm²
EAN	4744397013736	Connectable conductor cross section fine-strand with cable end sleeve	1.5 - 10 mm²
Classe ETIM	EC000897	Connectable conductor cross section solid-core	Inconnu
Serie de produits	Universal terminals OTL	Connectable conductor cross section multi-wired	1.5 - 16 mm²
Code CN8	85369010	Rated current I _n	82 A
Unité	pcs	Rated voltage	1500 V
Taille du paquet:	66	Type of electrical connection 1	Screw connection
Poids net	0,017 kg	Type of electrical connection 2	N'est pas applicable
Longueur nette	0,045 m	Number of levels	1
Largeur nette	0,0135 m	Number of clamp positions per level	2
Profondeur nette	0,0395 m	Mounting method	DIN rail (top hat rail) 35 mm
		Material insulation body	Thermoplastic
		Operating temperature	-25 - 80 °C
		Inflammability class of insulation material according - to UL94	
		Width	13.5 mm
		Height	39.5 mm
		Depth	45 mm
		Explosion-tested version 'Ex e'	Non
		Closing plate required	Non
		Colour	Grey
		Internally connected stages	Oui