



OTL50 rouge 1xAl/Cu 1,5-50mm²
1500V Bloc de jonction

MAA1050R10

Code produit	MAA1050R10
EAN	4744397013842
Classe ETIM	EC000897
Serie de produits	Universal terminals OTL
Code CN8	85369010
Unité	pcs
Taille du paquet:	48
Poids net	0,03 kg
Longueur nette	0,05 m
Largeur nette	0,018 m
Profondeur nette	0,043 m

Connectable conductor cross section fine-strand without cable end sleeve	1.5 - 35 mm²
Connectable conductor cross section fine-strand with cable end sleeve	1.5 - 35 mm²
Connectable conductor cross section solid-core	Inconnu
Connectable conductor cross section multi-wired	1.5 - 50 mm²
Rated current In	160 A
Rated voltage	1500 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	N'est pas applicable
Number of levels	1
Number of clamp positions per level	2
Mounting method	DIN rail (top hat rail) 35 mm
Material insulation body	Thermoplastic
Operating temperature	-25 - 80 °C
Inflammability class of insulation material according - to UL94	
Width	18 mm
Height	43 mm
Depth	50 mm
Explosion-tested version 'Ex e'	Non
Closing plate required	Non
Colour	Red
Internally connected stages	Oui