

OTL300 gris 1xAl/Cu 95-300mm²
1500V Universal terminal
MAA1300A10

Code produit	MAA1300A10	Connectable conductor cross section fine-strand without cable end sleeve	95 - 300 mm²
EAN	4744397035400	Connectable conductor cross section fine-strand with cable end sleeve	95 - 300 mm²
Classe ETIM	EC000897	Connectable conductor cross section solid-core	Inconnu
Serie de produits	Universal terminals OTL	Connectable conductor cross section multi-wired	95 - 300 mm²
Code CN8	85369010	Rated current In	490 A
Unité	pcs	Rated voltage	1500 V
Taille du paquet:	3	Type of electrical connection 1	Screw connection
Poids net	0,332 kg	Type of electrical connection 2	N'est pas applicable
Longueur nette	0,0106 m	Number of levels	1
Largeur nette	0,044 m	Number of clamp positions per level	2
0		Mounting method	DIN rail (top hat rail) 35 mm
		Material insulation body	Thermoplastic
		Operating temperature	-25 - 80 °C
		Inflammability class of insulation material according - to UL94	
		Width	44 mm
		Height	71 mm
		Depth	122 mm
		Explosion-tested version 'Ex e'	Non
		Closing plate required	Non
		Colour	Grey
		Internally connected stages	Oui