



OTL50-3 gris 3xAL/Cu 1,5-50mm²
1500V Bloc de jonction
MAA3050A10

Code produit	MAA3050A10
EAN	4744397014283
Classe ETIM	EC000897
Serie de produits	Universal terminals OTL
Code CN8	85369010
Unité	pcs
Taille du paquet:	24
Poids net	0,109 kg
Longueur nette	0,08 m
Largeur nette	0,046 m
Profondeur nette	0,041 m

Connectable conductor cross section fine-strand without cable end sleeve	1.5 - 35 mm²
Connectable conductor cross section fine-strand with cable end sleeve	1.5 - 35 mm²
Connectable conductor cross section solid-core	Inconnu
Connectable conductor cross section multi-wired	1.5 - 50 mm²
Rated current In	320 A
Rated voltage	1500 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	N'est pas applicable
Number of levels	1
Number of clamp positions per level	6
Mounting method	DIN rail (top hat rail) 35 mm
Material insulation body	Thermoplastic
Operating temperature	-25 - 80 °C
Inflammability class of insulation material according - to UL94	
Width	46 mm
Height	41 mm
Depth	80 mm
Explosion-tested version 'Ex e'	Non
Closing plate required	Non
Colour	Grey
Internally connected stages	Oui