



# THE PANEL 2 MICROPRISMATICO

102067.01

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: MICROPRISMATIZED  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: WITH ACCESSORY  
L: 1195mm  
A: 295mm  
H: 10mm  
Warranty: 5 years  
Weight: 3kg

## Tech data

Luminaire input power: 35W  
Luminaire luminous flux: 3672lm  
Luminous flux in emergency: 1h: 12% / 3h: 5%  
IP: 40  
Insulation class: II  
No. of driver per product: 1  
Supply voltage: 950mA aliment.incluso  
UGR: <19  
IK: IK07  
SELV: Si

## Source

Light source: LED  
Source power: 32W  
Source luminous flux: 4950lm  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[THE PANEL 2 MICROPRISMATICO: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 6/8/2025, 12:53:04












# THE PANEL 2 MICROPRISMATICO

102067.01

**novalux**

ITALIAN LIGHTING DESIGN SINCE 1948

## MOUNTING ACCESSORIES

	THE PANEL: STAFFE PLAFONE 600/1200	<b>16213.99</b>
	THE PANEL: N.4 SOSP. SNODATE L3000	<b>16230.99</b>
	THE PANEL: KIT MOLLE INC.CART.600/1200	<b>16215.99</b>
	THE PANEL: N.2 GIUNTI+N.2 SOSP.L3000 AN.	<b>16227.96</b>
	KIT ALIMENTAZIONE L1200 3P BIA	<b>108919.01</b>
	BOX PER INST. PLAFONE THE PANEL 1200X300	<b>102087.01</b>
	THE PANEL: SNODO 300 BIANCO NO SOSP.	<b>16234.01</b>
	THE PANEL: N.2 GIUNTI NON SOSPESI	<b>16232.96</b>
	THE PANEL 2: KIT INST.INC.RAS.CART.1200	<b>102029.99</b>
	KIT ALIMENTAZIONE L3000 3P BIA	<b>108920.01</b>
	THE PANEL 2: KIT ANTIC. L3000 +MORS.	<b>102031.99</b>




Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 6/8/2025, 12:53:04

# THE PANEL 2 MICROPRISMATICO

102067.01

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



THE PANEL 2: KIT PER BIN.1200X300 3P


**102054.01**



THE PANEL: KIT SOSP.600/1200 CAVI 4X3MT


**16223.99**

## EMERGENCY ACCESSORIES



THE PANEL 2: EMER.INC.3H 10/54VDC

**1020A5.99**



THE PANEL 2: EMER.INC.1H 10/54VDC

**1020A4.99**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 6/8/2025, 12:53:04