


P-30 READY

103335.20

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT
Optics: OPAL
Colour: CAFFE
Dimming: ON/OFF
Emergency: NO
L: 830mm
A: 830mm
H: 31mm
Made in: ITALY
Warranty: 5 years
Weight: 5.2kg

Tech data

Luminaire input power: 39.7W
Luminaire luminous flux: 3152lm
IP: 40
Insulation class: I
No. of driver per product: 2
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 32W
Source luminous flux: 5936lm
Colour temperature: 3000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10



Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[P-30 READY: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 12:53:58

103335.20

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

	P-30: ROSONE LATER. ALIM L=1200 3P BIA 103320.01
	P-30: ROSONE QDR CARTON. L1200 3P CAFFE 103319.20
	P-30: ROSONE DOPPIO CART . L=1200 3P CAF 103367.20
	P-30: ROSONE LATER. ALIM L1200 3P CAFFE 103320.20
	P-30: ROSONE LATER. DOPPIO L=1200 3P CAF 103368.20
	P-30: ROSONE QDR CARTON. L=1200 3P BIA 103319.01