

## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Beam: 36°  
Colour: SHINY BRUNISH  
Dimming: WITH ACCESSORY  
Emergency: WITH ACCESSORY  
H: 105mm  
ø: Ø65  
D: 60mm  
Warranty: 5 years  
Weight: 0.315kg

## Tech data

Luminaire luminous flux: 730lm  
Luminous flux in emergency: 1h: 44% / 3h: 18%  
IP: 20  
Insulation class: III  
Supply voltage: DC 500 mA  
UGR: <19  
SELV: No

## Source

Light source: LED  
Source power: 10W  
Source luminous flux: 945lm  
Colour temperature: 3000K  
CRI: >90  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[KONE: View more product info](#)



## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Colour: SHINY COPPER  
Warranty: 5 years  
Weight: 0.1kg

## Tech data

UGR: <19

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

### ELECTRICAL ACCESSORIES



ALIM. LED MAX 18W 500MA

**101325.99**


### DIMMABLE ACCESSORIES



ALIM. LED 26W 500MA/9-52V DALI/PUSH


**101334.99**

### EMERGENCY ACCESSORIES



KIT EMERGENZA 3H 10V-54V

**18005.99**



KIT EMERGENZA 1H 10V-54V

**18004.99**