




Features

Use: Indoor
 Type of installation: RECESSED INTO PLASTERBOARD
 Emission: DIRECT
 Optics: SPOT
 Beam: 36°
 Colour: BLACK
 Dimming: WITH ACCESSORY
 Emergency: WITH ACCESSORY
 H: 60mm
 ø: Ø40
 D: 35mm
 Warranty: 5 years
 Weight: 0.075kg

Tech data

Luminaire luminous flux: 273lm
 Luminous flux in emergency: 1h: 78% / 3h: 32%
 IP: 20
 Insulation class: III
 Supply voltage: DC 500 mA
 SELV: No



Source

Light source: LED
 Source power: 5W
 Colour temperature: 3000K
 CRI: >90
 LED lifespan: 50000h L80 B20

Compliance


CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[KONE: View more product info](#)



ELECTRICAL ACCESSORIES



ALIM. LED 6W/500MA 6-12V

101343.99



ALIM. LED MAX 18W 500MA

101325.99



ALIM. LED 14W 500MA/2-27V

101331.99


DIMMABLE ACCESSORIES



ALIM. LED 26W 500MA/9-52V DALI/PUSH


101334.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 3H 10V-54V

18005.99



KIT EMERGENZA 1H 10V-54V

18004.99