

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: LENS UGR<19
Colour: WHITE
Dimming: ON/OFF
Emergency: WITH ACCESSORY
L: 1125mm
A: 295mm
H: 14 (30 con alim.)mm
Warranty: 5 years
Weight: 3.37kg

Tech data

Luminaire input power: 33W
Luminaire luminous flux: 4100lm
Luminous flux in emergency: 1h: 13% / 3h: 5%
IP: 40
Insulation class: II
No. of driver per product: 1
Supply voltage: 900 mA ALIMENT.INCLUSO
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 30W
Source luminous flux: 5016lm
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.








Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).



[SCHOOL: View more product info](#)



MOUNTING ACCESSORIES

	<p>SCHOOL: KIT MOLLE PER INCASSO</p>	<p>104107.99</p>
	<p>SCHOOL: KIT ANTICADUTA L=3000</p>	<p>104119.99</p>
	<p>KIT ALIMENTAZIONE L1200 3P BIA</p>	<p>108919.01</p>
	<p>BOX PER INST. PLAFONE THE PANEL 1200X300</p>	<p>102087.01</p>
	<p>SCHOOL: KIT INST.PLAFONE 1200X300</p>	<p>104109.01</p>
	<p>THE PANEL 2: KIT INST.INC.RAS.CART.1200</p>	<p>102029.99</p>
	<p>SCHOOL: KIT SOSPENSIONE H1200</p>	<p>104110.99</p>

EMERGENCY ACCESSORIES

	<p>THE PANEL 2: EMER.INC.3H 10/54VDC</p>	<p>1020A5.99</p>
	<p>THE PANEL 2: EMER.INC.1H 10/54VDC</p>	<p>1020A4.99</p>