



Features

Use: Indoor
Type of installation: WALL, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: NO
L: Ø962mm
A: 40mm
H: 40mm
Made in: ITALY
Warranty: 5 years
Weight: 5.5kg

Tech data

Luminaire input power: 66.1W
Luminaire luminous flux: 4643lm
IP: 40
Insulation class: III
Supply voltage: MAX 1.8A
UGR: <19
IK: 3
SELV: Si

Source

Light source: LED
Source power: 62W
Source luminous flux: 8502lm
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[HALOS: View more product info](#)

[HALOS ACOUSTIC: View more product info](#)



COMPLETION ACCESSORIES

	ARK/HALOS: KIT GIUNZIONE PROFILI BIA	109809.01
---	--------------------------------------	-----------

MOUNTING ACCESSORIES

	CAVO ALIMENTAZIONE L=3000 2X1 BIANCO	109001.01
	CAVO ALIMENTAZIONE L=3000 3X1.5 TRASP	109001.00
	HALOS: ROSONE DOPPIA ALIM. REMOTA BIA	105158.01
	HALOS: KIT 4 CAVI SOSPENSIONE L.3000	105159.99
	HALOS: ROSONE ALIM. REMOTA BIA	105157.01
	CAVO ALIMENTAZIONE L=3000 2X1 NERO	109001.02

ELECTRICAL ACCESSORIES

	HALOS: ROSONE-N DOPPIA ALIM ON/OFF BIA	105155.01
	HALOS: ROSONE-N ALIM. ON/OFF BIA	105151.01
	HALOS: ROSONE ALIM. ON/OFF BIANCO	105149.01

	HALOS: ROSONE DOPPIA ALIM. ON/OFF BIA	105153.01
	HALOS: ALIMENTATORE ON/OFF	105147.99
DIMMABLE ACCESSORIES		
	HALOS: ROSONE-N ALIM. DALI/PUSH BIA	105152.01
	HALOS: ROSONE ALIM. DALI/PUSH BIANCO	105150.01
	HALOS: ALIMENTATORE DALI/PUSH	105148.99
	HALOS: ROSONE-N DOPPIA ALIM D/PUSH BIA	105156.01
	HALOS: ROSONE DOPPIA ALIM. DA/PUSH BIA	105154.01