



## Features

Use: Indoor  
Type of installation: SUSPENDED  
Emission: DIRECT/INDIRECT  
Optics: OPAL  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: NO  
L: 1196mm  
A: 296mm  
H: 11mm  
Warranty: 5 years  
Weight: 4.75kg

## Tech data

Luminaire input power: 37W  
Luminaire luminous flux: 4185lm  
Direct luminous flux: 2780lm  
Indirect luminous flux: 1405lm  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
UGR: <19  
IK: IK07  
SELV: Si

## Source

Light source: LED  
Source power: 33W  
Source luminous flux: 5020lm  
Colour temperature: 3000K  
CRI: >80  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[THE PANEL BIEMISSIONE: View more product info](#)



# THE PANEL BIEMISSIONE

105601.01

## MOUNTING ACCESSORIES

---



THE PANEL: N.2 GIUNTI NON SOSPESI

**16232.96**

