



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: OPAL
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: 1196mm
A: 296mm
H: 11mm
Warranty: 5 years
Weight: 4.75kg

Tech data

Luminaire input power: 37W
Luminaire luminous flux: 4545lm
Direct luminous flux: 3020lm
Indirect luminous flux: 1525lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
UGR: <19
IK: IK07
SELV: Si

Source

Light source: LED
Source power: 33W
Source luminous flux: 5450lm
Colour temperature: 4000K
CRI: >80
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[THE PANEL BIEMISSIONE: View more product info](#)



THE PANEL BIEMISSIONE

105602.01

MOUNTING ACCESSORIES



THE PANEL: N.2 GIUNTI NON SOSPESI

16232.96