


P-30 PCB

105831.21

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: WALL
Emission: DIRECT
Optics: OPAL
Colour: CAPPUCCINO
Dimming: ON/OFF
Emergency: NO
L: 2400mm
A: 31mm
H: 31mm
Made in: ITALY
Warranty: 5 years
Weight: 2.4kg

Tech data

Luminaire input power: 28W
Luminaire luminous flux: 2363lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 24W
Source luminous flux: 4452lm
Colour temperature: 3000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[P-30 PCB: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 12:56:24

P-30 PCB

105831.21

SCREENS



P-30: DIFF. OPALE PER L2400

103314.99



P-30: DIFF. OPALE L=6500

103315.99

COMPLETION ACCESSORIES



P-30: ANGOLO L PLAFONE-SOSP-PARETE CAPP

103327.21




P-30: COVER ANGOLO L CAPP

103329.21




P-30: TESTATE PLAF/SOSP/PAR/SPOT CAPP

103361.21



P-30: SNODO 3P PER PCB/STRIP CAPP

105853.21



P-30: SNODO NO CAVI CAPP

105854.21

