



Features

Use: Indoor
Type of installation: TRACK
Emission: DIRECT
Optics: MICRO OPTICS
Beam: 76°
Colour: BLACK
Dimming: DALI
Emergency: NO
L: 300mm
A: 11mm
H: 7mm
Made in: ITALY
Warranty: 5 years
Weight: 0.025kg

Tech data

Luminaire input power: 7W
Luminaire luminous flux: 403lm
IP: 20
Insulation class: III
Supply voltage: 48 Vdc
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 5W
Source luminous flux: 454lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[T-48 MINI: View more product info](#)

[L-16 TRACK: View more product info](#)

