



Features

Use: Indoor

Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK

Emission: DIRECT

Optics: MICRO OPTICS

Colour: CAFFE

Dimming: PUSH, DALI

Emergency: NO

L: 868mm

A: 53mm

H: 69mm

Made in ITALY

Warranty: 5 years

Tech data

Luminaire input power: 26.5W

Luminaire luminous flux: 2134lm

IP: 40

Insulation class: I

No. of driver per product: 1

Supply voltage: 220-240V 50/60Hz

UGR: <19

SELV: Sì

Source

Light source: LED

Source power: 22W

Colour temperature: 2700K

CRI: >90

Colour tolerance: 3 Step MacAdam

LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[HERO: View more product info](#)

COMPLETION ACCESSORIES

 Diagram showing a side view of a rectangular profile with dimensions: H 135, L 250, W 33.	HERO: MOD.CIECO 250 CAF	108676.20
 Diagram showing a side view of a rectangular profile with dimensions: H 135, L 1400, W 33.	HERO: MOD.CIECO 1400 CAF	108680.20
 Diagram showing an L-shaped profile with dimensions: H 135, L 150, W 33.	HERO: MOD.CIECO ANG.SX 150 CAF	108677.20
 Diagram showing a side view of a rectangular profile with dimensions: H 135, L 1680, W 33.	HERO: MOD.CIECO 1680 CAF	108681.20
 Diagram showing two small rectangular profiles with dimensions: H 135, L 33, W 33.	HERO: COPPIA TESTATE CAF	108684.20
 Diagram showing an L-shaped profile with dimensions: H 135, L 150, W 33.	HERO: MOD.CIECO ANG.DX 150 CAF	108678.20
 Diagram showing a side view of a rectangular profile with dimensions: H 135, L 1120, W 33.	HERO: MOD.CIECO 1120 CAF	108679.20

MOUNTING ACCESSORIES

 Diagram showing a cable with a connector and dimensions: H 12, L 17.	KIT ALIMENTAZIONE L1200 5P BIA	108921.01
 Diagram showing a cable with a connector and dimensions: H 12, L 17.	HERO: SOSPL3000 1PZ TESTA W.G.BASSO	108685.99
 Diagram showing a cable with a connector and dimensions: H 12, L 17.	KIT ALIMENTAZIONE L3000 5P BIA	108922.01

	KIT ALIMENTAZIONE L3000 5P CAF	108922.20
	HERO: SPESS. CARTONG. 10MM 2PZ.	108689.99
	HERO: SOSPL3000 1PZ UNIONE W.G.BASSO	108686.99
	ALL-TRACK: COPPIA ADATT. 3P+DALI NER	106723.02
	HERO: STAFFA PARETE "L" CAF	108687.20
	ALL-TRACK: COPPIA ADATT. 3P+DALI BIA	106723.01
	HERO: SOSPL3000 1PZ TESTA W.G.ALTO	1086A1.99
	KIT ALIMENTAZIONE L1200 5P CAF	108921.20
	HERO: KIT INCASSO LED (1X)	108688.99
	HERO: SOSPL3000 1PZ UNIONE W.G.ALTO	1086A2.99