



## Features

Use: Indoor  
 Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
 Emission: DIRECT  
 Optics: SPOT  
 Beam: 14°  
 Colour: WHITE  
 Dimming: PUSH, DALI  
 Emergency: NO  
 L: 1120mm  
 A: 53mm  
 H: 69mm  
 Made in: ITALY  
 Warranty: 5 years  
 Weight: 3.4kg

## Tech data

Luminaire input power: 29W  
 Luminaire luminous flux: 2028lm  
 IP: 40  
 Insulation class: I  
 No. of driver per product: 1  
 Supply voltage: 220-240V 50/60Hz  
 SELV: Si

## Source

Light source: LED  
 Source power: 2X13W  
 Source luminous flux: 2644lm  
 Colour temperature: 2700K  
 CRI: >90  
 Colour tolerance: 3 Step MacAdam  
 LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[HERO: View more product info](#)



## COMPLETION ACCESSORIES

	HERO: MOD.CIECO ANG.SX 150 BIA	<b>108677.01</b>
	HERO: MOD.CIECO 1680 BIA	<b>108681.01</b>
	HERO: MOD.CIECO 1400 BIA	<b>108680.01</b>
	HERO: COPPIA TESTATE BIA	<b>108684.01</b>
	HERO: MOD.CIECO 250 BIA	<b>108676.01</b>
	HERO: MOD.CIECO 1120 BIA	<b>108679.01</b>
	HERO: MOD.CIECO ANG.DX 150 BIA	<b>108678.01</b>

## MOUNTING ACCESSORIES

	KIT ALIMENTAZIONE L1200 5P BIA	<b>108921.01</b>
	HERO: SOSPL.3000 1PZ TESTA W.G.BASSO	<b>108685.99</b>
	KIT ALIMENTAZIONE L3000 5P BIA	<b>108922.01</b>



HERO: STAFFA PARETE "L" BIA

**108687.01**



HERO: SPESS. CARTONG. 10MM 2PZ.

**108689.99**



HERO: SOSPL.3000 1PZ UNIONE W.G.BASSO

**108686.99**



ALL-TRACK: COPPIA ADATT. 3P+DALI BIA

**106723.01**



HERO: SOSPL.3000 1PZ TESTA W.G.ALTO

**1086A1.99**



HERO: KIT INCASSO LED (1X)

**108688.99**



HERO: SOSPL.3000 1PZ UNIONE W.G.ALTO

**1086A2.99**