



## Features

Use: Indoor  
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Beam: 36°  
Colour: CAFFE  
Dimming: PUSH, DALI  
Emergency: Autonomy 3h/Recharge time 24h  
L: 250mm  
A: 53mm  
H: 69mm  
Made in: ITALY  
Warranty: 5 years except battery

## Tech data

Luminaire input power: 5W  
Luminaire luminous flux: 140lm  
Luminous flux in emergency: 100%  
IP: 40  
Insulation class: I  
Supply voltage: 220-240V 50/60Hz  
SELV: No

## Source

Light source: LED  
Source power: 1W  
Colour temperature: 4500K  
CRI: >80

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012, CEI EN 60598-2-22:2023

## Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[HERO: View more product info](#)

# HERO

108699.20

novalux

ITALIAN LIGHTING DESIGN SINCE 1948

## COMPLETION ACCESSORIES

---



HERO: COPPIA TESTATE CAF

108684.20



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 6/8/2025, 12:51:20