

Features

Use: Indoor
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK
Emission: DIRECT
Optics: OPAL FULL LIGHT
Colour: CAPPUCCINO
Dimming: PUSH, DALI
Emergency: NO
L: 2240mm
A: 53mm
H: 69mm
Made in: ITALY
Warranty: 5 years
Weight: 5.6kg

Tech data

Luminaire input power: 78.1W
Luminaire luminous flux: 6340lm
IP: 40
Insulation class: I
No. of driver per product: 2
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 65W
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)




Features

Use: Indoor
Optics: OPAL FULL LIGHT
L: 2240mm
A: 52.5mm
H: 15mm
Made in: ITALY
Warranty: 5 years
Weight: 0.13kg

Tech data

IP: 40



COMPLETION ACCESSORIES

	HERO: MOD.CIECO 250 CAP	108676.21
	HERO: MOD.CIECO ANG.SX 150 CAP	108677.21
	HERO: MOD.CIECO ANG.DX 150 CAP	108678.21
	HERO: MOD.CIECO 1120 CAP	108679.21
	HERO: MOD.CIECO 1400 CAP	108680.21
	HERO: MOD.CIECO 1680 CAP	108681.21
	HERO: COPPIA TESTATE CAP	108684.21

MOUNTING ACCESSORIES

	HERO: SOSPL3000 1PZ TESTA W.G.ALTO	1086A1.99
	HERO: SOSPL3000 1PZ UNIONE W.G.ALTO	1086A2.99
	ALL-TRACK: COPPIA ADATT. 3P+DALI BIA	106723.01
	ALL-TRACK: COPPIA ADATT. 3P+DALI NER	106723.02

	HERO: SOSP.L3000 1PZ. TESTA/CODA	108685.99
	HERO: SOSP.L3000 1PZ. UNIONE	108686.99
	HERO: STAFFA PARETE "L" CAP	108687.21
	HERO: KIT INCASSO LED (1X)	108688.99
	HERO: SPESS. CARTONG. 10MM 2PZ.	108689.99
	KIT ALIMENTAZIONE L1200 5P CAP	108921.21
	KIT ALIMENTAZIONE L3000 5P CAP	108922.21