




# HERO B

108731.21

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: SUSPENDED  
Emission: DIRECT/INDIRECT  
Optics: MICRO OPTICS  
Colour: CAPPUCCINO  
Dimming: ON/OFF  
Emergency: NO  
L: 1428mm  
A: 53mm  
H: 92mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 5kg

## Tech data

Luminaire input power: 69W  
Luminaire luminous flux: 6323lm  
Direct luminous flux: 3556lm  
Indirect luminous flux: 2767lm  
IP: 40  
Insulation class: I  
No. of driver per product: 2  
Supply voltage: 220-240V 50/60Hz  
UGR: <19  
SELV: Si

## Source

Light source: LED  
Source power: 61W  
Colour temperature: 2700K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

[HERO B: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 6/8/2025, 13:04:53

## COMPLETION ACCESSORIES

|                                                                                     |                                  |                  |
|-------------------------------------------------------------------------------------|----------------------------------|------------------|
|    | HERO B: MOD.CIECO 250 CAP        | <b>1087A3.21</b> |
|    | HERO B: MOD.CIECO ANG.SX 150 CAP | <b>1087A4.21</b> |
|    | HERO B: MOD.CIECO ANG.DX 150 CAP | <b>1087A5.21</b> |
|    | HERO B: MOD.CIECO 1120 CAP       | <b>1087A6.21</b> |
|   | HERO B: MOD.CIECO 1400 CAP       | <b>1087A7.21</b> |
|  | HERO B: MOD.CIECO 1680 CAP       | <b>1087A8.21</b> |
|  | HERO B: COPPIA TESTATE CAP       | <b>1087B1.21</b> |

## MOUNTING ACCESSORIES

|                                                                                     |                                   |                  |
|-------------------------------------------------------------------------------------|-----------------------------------|------------------|
|   | HERO B: KIT COPPIA CAVI SOSP. 5 M | <b>1087B2.99</b> |
|  | KIT ALIMENTAZIONE L1200 3P BIA    | <b>108919.01</b> |
|  | KIT ALIMENTAZIONE L1200 3P CAP    | <b>108919.21</b> |

# HERO B

108731.21

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



KIT ALIMENTAZIONE L3000 3P BIA

**108920.01**



KIT ALIMENTAZIONE L3000 3P CAP

**108920.21**



Novalux S.r.l. via Marzabotto, 2 40050 Fano di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 6/8/2025, 13:04:53