


# HERO B

**108767.21**






## Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: SPOT
Beam: 14°
Colour: CAPPUCCINO
Dimming: DALI
Emergency: NO
L: 1120mm
A: 53mm
H: 92mm
Made in: ITALY
Warranty: 5 years
Weight: 2.5kg

## Tech data

Luminaire input power: 48.5W
Luminaire luminouse flux: 4104lm
Direct luminous flux: 2028lm
Indirect luminous flux: 2076lm
IP: 40
Insulation class: I
No. of driver per product: 2
Supply voltage: 220-240V 50/60Hz
SELV: Sì

## Source

Light source: LED
Source power: 2x13+18W
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 1Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

HERO B: View more product info

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh



**This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.**
**Last update: 6/8/2025, 13:04:44**

# HERO B

**108767.21**

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

## COMPLETION ACCESSORIES

| | | |
|---|---|---|
|  | HERO B: MOD.CIECO 250 CAP | **1087A3.21** |
|  | HERO B: MOD.CIECO ANG.SX 150 CAP | **1087A4.21** |
|  | HERO B: MOD.CIECO ANG.DX 150 CAP | **1087A5.21** |
|  | HERO B: MOD.CIECO 1120 CAP | **1087A6.21** |
|  | HERO B: MOD.CIECO 1400 CAP | **1087A7.21** |
|  | HERO B: MOD.CIECO 1680 CAP | **1087A8.21** |
|  | HERO B: COPPIA TESTATE CAP | **1087B1.21** |

## MOUNTING ACCESSORIES

| | | |
|---|---|---|
|  | HERO B: KIT COPPIA CAVI SOSP. 5 M | **1087B2.99** |
|  | KIT ALIMENTAZIONE L1200 5P BIA | **108921.01** |
|  | KIT ALIMENTAZIONE L3000 5P BIA | **108922.01** |

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh



**This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.**
**Last update: 6/8/2025, 13:04:44**