

Features

Use: Indoor
Type of installation: RECESSED, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: CAPPUCCINO
Dimming: WITH ACCESSORY
Emergency: NO
A: 40mm
H: 40mm
ø: 962mm
Made in: ITALY
Warranty: 5 years
Weight: 4.2kg

Tech data

Luminaire input power: 44.8W
Luminaire luminous flux: 1951lm
IP: 40
Insulation class: III
Supply voltage: MAX 1.8A
UGR: <19
SELV: No

Source

Light source: LED
Source power: 42W
Source luminous flux: 5668lm
Colour temperature: 2700K
CRI: >90
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards


Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[ARK: View more product info](#)

COMPLETION ACCESSORIES

	ARK/HALOS: KIT GIUNZIONE PROFILI NE	109809.02
	ARK/HALOS: KIT GIUNZIONE PROFILI BIA	109809.01

MOUNTING ACCESSORIES

	CAVO ALIMENTAZIONE L=3000 3X1.5 TRASP	109001.00
	HALOS: ROSONE ALIM. REMOTA CAPP	105157.21
	HALOS: KIT 4 CAVI SOSPENSIONE L.3000	105159.99
	HALOS: ROSONE DOPPIA ALIM. REMOTA CAPP	105158.21
	ARK: KIT INCASSO PER 962	109807.99

ELECTRICAL ACCESSORIES

	HALOS: ROSONE-N ALIM. ON/OFF CAPP	105151.21
	HALOS: ROSONE-N DOPPIA ALIM ON/OFF CAPP	105155.21
	HALOS: ALIMENTATORE ON/OFF	105147.99

DIMMABLE ACCESSORIES



HALOS: ALIMENTATORE DALI/PUSH

105148.99



HALOS: ROSONE-N DOPPIA ALIM D/PUSH CAPP

105156.21



HALOS: ROSONE-N ALIM. DALI/PUSH CAPP

105152.21