VISaVIS

111001.05



Features

Use: Outdoor
Type of installation: TABLE LAMP
Emission: DIRECT/INDIRECT
Optics: OPAL
Colour: ROSSO
Dimming: PUSH
Emergency: NO
H: 380mm
ø: Ø100
Warranty: 3 years except battery
Weight: 0.91kg

Tech data

Luminaire luminouse flux: 190lm
IP: 65
Insulation class: III

Source

Light source: LED
Source power: 2W
Colour temperature: 2.2/2.7/3.0K
CRI: >80
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

VISaVIS: View more product info

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 12:50:49

VISaVIS

111001.05

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

ELECTRICAL ACCESSORIES

	VIS A VIS: RICAMBIO BATTERIA	**111003.99**
	VIS A VIS: BASE PER RICARICA MAX 6 PCS	**111002.02**

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 12:50:49