



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT
Optics: SPOT
Colour: LIGHT GREY
H: 200mm
ø: 55mm
Made in: EU
Warranty: 5 years


Tech data

Insulation class: I
Supply voltage: 220-230V 50/60 Hz

Source

Socket: GU10 (lamp not included)
Source power: MAX 10W LED

[COLLINS SP: View more product info](#)



SCREENS



DIFFUSORE D.55 OPALE X SPOT BI/NE/LG/DG

112903.99

MOUNTING ACCESSORIES



ROSONE CIRCOLARE 3 X D. 200 DARK GREY

112908.24



ROSONE LINEA. 12X ORIZZONTALI L.780 BIAN

112916.01



ROSONE CIRCOLARE 3 X D. 200 NERO

112908.02



BRIDGE SYSTEM: RACCORDO PASSACAVO SENZA FORO 5PZ BIANCO

112920.01



ROSONE TONDO 4X ORIZZONTALI D180 BI

112913.01



ROSONE INCASSO DIAM. 40 NERO

112906.02



ROSONE TONDO 4X ORIZZONTALI D180 NE

112913.02



ROSONE LINEARE 3 X L=620 NERO

112907.02



ROSONE CIRCOLARE 3 X D. 200 LIGHT GREY

112908.23

	ROSONE TONDO 12X ORIZZONTALI D300 NE	112914.02
	ROSONE INCASSO DIAM. 40 LIGHT GREY	112906.23
	ROSONE TONDO 12X ORIZZONTALI D300 BI	112914.01
	BRIDGE SYSTEM: RACCORDO PASSACAVO SENZA FORO 5PZ NERO	112920.02
	ROSONE PLAFONE D. 55 NERO	112905.02
	ROSONE PLAFONE D. 55 LIGHT GREY	112905.23
	ROSONE LINEARE 3 X L=620 LIGHT GREY	112907.23
	ROSONE PLAFONE D. 55 BIANCO	112905.01
	ROSONE LINEA. 12X VERTICALI L.1500 NERO	112917.02
	ROSONE PLAFONE D. 55 DARK GREY	112905.24
	ROSONE LINEARE 3 X L=620 BIANCO	112907.01