



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT
Optics: SPOT
Colour: DARK GREY
H: 350mm
ø: 65mm
Made in: EU
Warranty: 5 years


Tech data

Insulation class: I
Supply voltage: 220-230V 50/60 Hz

Source

Socket: GU10 (lamp not included)
Source power: MAX 10W LED

[CRYSTAL : View more product info](#)



MOUNTING ACCESSORIES

	ROSONE CIRCOLARE 3 X D. 200 DARK GREY	112908.24
	ROSONE LINEA. 12X ORIZZONTALI L.780 BIAN	112916.01
	ROSONE CIRCOLARE 3 X D. 200 NERO	112908.02
	BRIDGE SYSTEM: RACCORDO PASSACAVO SENZA FORO 5PZ BIANCO	112920.01
	ROSONE TONDO 4X ORIZZONTALI D180 BI	112913.01
	ROSONE INCASSO DIAM. 40 NERO	112906.02
	ROSONE TONDO 4X ORIZZONTALI D180 NE	112913.02
	ROSONE LINEARE 3 X L=620 NERO	112907.02
	ROSONE CIRCOLARE 3 X D. 200 LIGHT GREY	112908.23
	ROSONE INCASSO DIAM. 40 BIANCO	112906.01
	BRIDGE SYSTEM: ADAT. ALL-TRACK ELET/MEC ON/OFF C/MORS B	112922.01



ROSONE LINEA. 12X VERTICALI L.1500 BIAN

112917.01



ROSONE INCASSO DIAM. 40 DARK GREY

112906.24



ROSONE TONDO 12X VERTICALI D350 BI

112915.01



ROSONE LINEA. 12X ORIZZONTALI L.780 NERO

112916.02



ROSONE TONDO 12X VERTICALI D350 NE

112915.02



ROSONE CIRCOLARE 3 X D. 200 BIANCO

112908.01



BRIDGE SYSTEM: RACCORDO PASSACAPO CON FORO 5PZ NERO

112921.02



ROSONE LINEARE 3 X L=620 DARK GREY

112907.24



BRIDGE SYSTEM: ADAT. ALL-TRACK ELET/MEC ON/OFF C/MORS N

112922.02



BRIDGE SYSTEM: RACCORDO PASSACAPO CON FORO 5PZ BIANCO

112921.01



ROSONE TONDO 12X ORIZZONTALI D300 NE

112914.02



ROSONE INCASSO DIAM. 40 LIGHT GREY

112906.23





ROSONE TONDO 12X ORIZZONTALI D300 BI

112914.01

BRIDGE SYSTEM: RACCORDO PASSACAVO SENZA FORO 5PZ NERO

112920.02

ROSONE PLAFONE D. 55 NERO

112905.02

ROSONE PLAFONE D. 55 LIGHT GREY

112905.23

ROSONE LINEARE 3 X L=620 LIGHT GREY

112907.23

ROSONE PLAFONE D. 55 BIANCO

112905.01

ROSONE LINEA. 12X VERTICALI L.1500 NERO

112917.02

ROSONE PLAFONE D. 55 DARK GREY

112905.24

ROSONE LINEARE 3 X L=620 BIANCO

112907.01