



## Features

Use: Indoor  
Type of installation: WALL, SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: MICROPRISMATIZED  
Colour: CAFFE  
Dimming: PUSH, DALI  
Emergency: NO  
H: 70mm  
ø: 610mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 6,0kg

## Tech data

Luminaire input power: 57W  
Luminaire luminous flux: 5476lm  
IP: 40  
Insulation class: I  
No. of driver per product: 2  
Supply voltage: 220-240V 50/60Hz  
UGR: <19  
SELV: Sì

## Source

Light source: LED  
Source power: 49W  
Source luminous flux: 7778lm  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[ROTO EVO: View more product info](#)

# ROTO EVO

113112.20

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## MOUNTING ACCESSORIES

---



ROTO EVO: KIT SOSPENSIONE L=3000 1PZ

**113137.99**

---



ROTO EVO: KIT PLAFONE/PARETE D.610

**113138.99**

---



ROSONE 5X1,5 TND 3000 CAF

**109007.20**



Novalux S.r.l. via Marzabotto, 2 40050 Fano di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 6/8/2025, 12:48:54