
# HERO MINI B | CAOS | CAOS B | HERO MINI

**113211.02**






## Features

Use: Indoor
Optics: MICRO OPTICS
Beam: 40°
Colour: BLACK
Dimming: WITH ACCESSORY
Emergency: NO
L: 636mm
A: 30mm
H: 24mm
Made in: ITALY
Warranty: 5 years

## Tech data

Luminaire input power: 20W
Luminaire luminouse flux: 1708lm
IP: 40
Insulation class: III
Supply voltage: DC 700 MA
UGR: <19

## Source

Light source: LED
Source power: 17W
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

HERO MINI B: View more product info

CAOS: View more product info

CAOS B: View more product info

HERO MINI: View more product info

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh



**This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.**
**Last update: 6/8/2025, 12:49:32**