

Features

Use: Indoor
 Type of installation: RECESSED INTO PLASTERBOARD, CEILING MOUNTED
 Emission: DIRECT
 Optics: MICROPRISMATIZED
 Colour: WHITE
 Dimming: ON/OFF
 Emergency: WITH ACCESSORY
 L: 595mm
 A: 595mm
 H: 35mm
 Warranty: 3 years
 Weight: 2.47kg

Tech data

Luminaire input power: 36W
 Luminaire luminous flux: 3892lm
 Luminous flux in emergency: 1h: 12% / 3h: 5
 IP: 40
 Insulation class: II
 No. of driver per product: 1
 Supply voltage: 900mA driver incluso
 UGR: <19 4H-8H S=0,25
 IK: 5
 SELV: Sì

Source

Light source: LED
 Source power: 32W
 Source luminous flux: 4754lm
 Colour temperature: 4000K
 CRI: >80
 LED lifespan: 50000h L80 B20




Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012


Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.


MOUNTING ACCESSORIES

	KIT ALIMENTAZIONE L1200 5P BIA	108921.01
	KIT ALIMENTAZIONE L3000 5P BIA	108922.01
	KIT ALIMENTAZIONE L1200 3P BIA	108919.01
	BACKLIT: KIT ANTICADUTA	113639.99
	BACKLIT: KIT MOLLE INC.CART.600/1200 MG	113620.99
	THE PANEL 2: KIT INST.INC.RAS.CART.1200	102029.99
	BACKLIT: BOX PER INST. SOSP.1200X300 BIA	113638.01
	BACKLIT: BOX PER INST. PLAF. 600X600 BIA	113610.01
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01

EMERGENCY ACCESSORIES

	THE PANEL 2: EMER.INC.3H 10/54VDC	1020A5.99
--	-----------------------------------	-----------





THE PANEL 2: EMER.INC.1H 10/54VDC

1020A4.99