

Features

Use: Indoor
 Type of installation: RECESSED INTO PLASTERBOARD, CEILING MOUNTED
 Emission: DIRECT
 Optics: MICROPRISMATIZED
 Colour: WHITE
 Dimming: PUSH, DALI
 Emergency: WITH ACCESSORY
 L: 1195mm
 A: 295mm
 H: 35mm
 Warranty: 3 years
 Weight: 3.2kg

Tech data

Luminaire input power: 36W
 Luminaire luminous flux: 4080lm
 Luminous flux in emergency: 1h: 12% / 3h: 5
 IP: 40
 Insulation class: II
 No. of driver per product: 1
 Supply voltage: 900mA driver incluso
 UGR: <19 4H-8H S=0,25
 IK: 5
 SELV: Si

Source

Light source: LED
 Source power: 32W
 Source luminous flux: 5149lm
 Colour temperature: 4000K
 CRI: >80
 LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.




MOUNTING ACCESSORIES




BACKLIT: BOX PER INST. PLAF. 1200X300 BI

113611.01**EMERGENCY ACCESSORIES**



THE PANEL 2: EMER.INC.3H 10/54VDC

1020A5.99

THE PANEL 2: EMER.INC.1H 10/54VDC

1020A4.99