

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: OPAL
Beam: 100°
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
L: 110mm
A: 110mm
H: 24mm
Warranty: 5 years
Weight: 0.35kg

Tech data

Luminaire input power: 11W
Luminaire luminous flux: 959lm
Luminous flux in emergency: 1h: 53% / 3h: 21%
IP: 40
Insulation class: II
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 9W
Colour temperature: 4000K
CRI: >90
LED lifespan: 50000h L80 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[SLIM: View more product info](#)


DIMMABLE ACCESSORIES



ALIM. LED 18.2W 350MA/9-52V DALI/PUSH


101333.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 3H 10V-54V

18005.99



KIT EMERGENZA 1H 10V-54V

18004.99