

LESELI downlight



- * LED source integrated in downlight luminaries.
- * Connection to mains with screw terminals.
- * Well diffused light output, ideal for the general lighting of the ambient.
- * Thermally conductive body; extremely light and manageable.
- * Complete with springs for easy fastening on false ceilings.
- * Internal power supply.
- * Working Temperature: -20°C +40°C.
- * White bezel.
- * IP43

Item Characteristics

Code	D82540
Lamp Voltage	220-240 V
Nominal Power	24 W
Base	cavi/wires
Lamp Current	0,11 A
Nominal Flux	2200 LUMEN
Rated Flux	0 LUMEN
Light Tonality	Natural white
Colour temperature	4000 K
Opening beam	90°
Diameter	230 mm
Lenght	61 mm

Performance

Axis cd	1010
Irc/Ra	>80
Lifetime	25000 h
Energy Class	A+
kWh/1000h	24

Tech Info

Dimmable	NO
Number of ON-OFF cycles	100000
Power Factor	0,94
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2006/95/CE * Bassa Tensione 2004/108/CE * Compatibilità Elettromagnetica 2011/65/UE * RoHS 2012/19/UE * RAEE EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3-2 * anno 2007 EN 61000-3-2/A1/A2 * anno 2011 EN 61000-3-3 * anno 2014 EN 60598-1 EN 60598-2-2 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling

Shipping info

Item barcode	8011905843205
Pack	1 pz
Master barcode	8011905788483